

Tesco 99 Octane Forecourt Fuel



Test	Method	Units	Results
Appearance	Visual		Bright and Clear
Density at 15°C	ASTM D4052	kg/l	0.7429
Research Octane Number	BS 2637		99
Motor Octane Number	BS 2638		87.6
Oxygen Content	Calculated	% (m/m)	2.7
I.B.P	ISO 3405	°C	25.9
10% v rec. at	ISO 3405	°C	42.6
50% v rec. at	ISO 3405	°C	82.5
90% v rec. at	ISO 3405	°C	153.4
F.B.P	ISO 3405	°C	191.9
% v evap. at 70°C	ISO 3405	vol %	44.8
% v evap. at 100°C	ISO 3405	vol %	59.8
% v evap. at 150°C	ISO 3405	vol %	89.1
Recovery	ISO 3405	vol %	98.0
Residue	ISO 3405	vol %	1.0
Vapour pressure at 37.8°C	EN/ISO 13016-1pr	kPa	88.5
Aromatics	ASTM D1319	vol %	30.5
Olefins	ASTM D1319	vol %	4.3
Benzene	EN 238	vol %	0.4
Sulphur	ISO 8754	mg/kg	7.1
M.T.B.E	IP 466	vol %	5.0
T.B.E.E	IP 466	vol %	< 0.1
T.A.M.E	IP 466	vol %	< 0.1
Methanol	IP 466	vol %	< 0.1
I.P.A	IP 466	vol %	< 0.1
Ethanol	IP 466	vol %	4.9
Sec-Butanol	IP 466	vol %	< 0.1
N-Propanol	IP 466	vol %	< 0.1
1-Butanol	IP 466	vol %	< 0.1

All Greenergy fuels are designed for optimum operating and emissions performance.
For further information phone 020 7404 7700.