

99 Octane Unleaded Petrol

Date of sampling: 08.08.2017

Samples taken by: independent inspectors

TEST	UNIT	METHOD	RESULT
Appearance		Visual	Clear & bright
RON		IP 237	99.0
MON		IP 236	88.0
Density at 15°C	kg/m ³	IP 365	759.6
Lead	mg/l	IP 428	< 2.5
Sulphur content	mg/kg	IP 490	< 3.0
Copper corrosion 3 hrs at 50°C		IP 154	1a
Benzene	% (v/v)	IP 429	0.5
M.T.B.E	% (v/v)	IP 466	4.7
E.T.B.E	% (v/v)	IP 466	< 0.2
Methanol	% (v/v)	IP 466	< 0.2
Ethanol	% (v/v)	IP 466	4.8
Iso-Propanol	% (v/v)	IP 466	< 0.2
Sec-Butanol	% (v/v)	IP 466	< 0.2
T.A.M.E	% (v/v)	IP 466	< 0.2
Tert-Butanol	% (v/v)	IP 466	< 0.2
Iso-Butanol	% (v/v)	IP 466	< 0.2
Oxygen content	% (m/m)	IP 466	2.60
Vapour pressure	kPa	IP 394	55.8
I.B.P	°C	EN ISO 3405	35.1
10% v rec. at	°C	EN ISO 3405	54.3
50% v rec. at	°C	EN ISO 3405	102.3
90% v rec. at	°C	EN ISO 3405	153.0
F.B.P	°C	EN ISO 3405	192.0
% v evap. at 70°C	% (v/v)	EN ISO 3405	31.1
% v evap. at 100°C	% (v/v)	EN ISO 3405	48.3
% v evap. at 150°C	% (v/v)	EN ISO 3405	88.0
Residue	% (v/v)	EN ISO 3405	1.0
Aromatics	% (v/v)	IP 156	34.7
Olefins	% (v/v)	IP 156	4.7