

Unleaded Petrol

Date of sampling: 26.04.2019

Samples taken by: independent inspectors

TEST	UNIT	METHOD	RESULT
Appearance		Visual	Clear & bright
RON		IP 237	95.0
MON		IP 236	85.4
Density at 15°C	kg/m ³	IP 365	732.3
Lead	mg/l	IP 428	< 2.5
Sulphur content	mg/kg	IP 490	5.7
Copper corrosion 3 hrs at 50°C		IP 154	1a
Benzene	% (v/v)	IP 429	0.8
M.T.B.E	% (v/v)	IP 466	3.0
E.T.B.E	% (v/v)	IP 466	< 0.2
Methanol	% (v/v)	IP 466	< 0.2
Ethanol	% (v/v)	IP 466	4.8
Iso-Propanol	% (v/v)	IP 466	< 0.2
Sec-Butanol	% (v/v)	IP 466	< 0.2
T.A.M.E	% (v/v)	IP 466	0.8
Tert-Butanol	% (v/v)	IP 466	< 0.2
Iso-Butanol	% (v/v)	IP 466	< 0.2
Oxygen content	% (m/m)	IP 466	2.49
Vapour pressure	kPa	IP 394	91.4
I.B.P	°C	EN ISO 3405	25.7
10% v rec. at	°C	EN ISO 3405	40.8
50% v rec. at	°C	EN ISO 3405	75.5
90% v rec. at	°C	EN ISO 3405	141.9
F.B.P	°C	EN ISO 3405	181.9
% v evap. at 70°C	% (v/v)	EN ISO 3405	46.4
% v evap. at 100°C	% (v/v)	EN ISO 3405	65.4
% v evap. at 150°C	% (v/v)	EN ISO 3405	93.0
Aromatics	% (v/v)	IP 156	26.6
Olefins	% (v/v)	IP 156	5.4